

SATURN

ARCHITECT 1. 0




This series has been certified as an **"ECO-FRIENDLY BUILDING MATERIAL"** by the Singapore Environmental Council

024-014-2606



space
Ceramics + Porcelain





WHITE
MATT



IVORY
MATT



WHITE
POLISHED



IVORY
POLISHED



IVORY
STRUCTURED  R10



BEIGE
MATT 



GREY
MATT 



BEIGE
POLISHED



GREY
POLISHED



GREY
STRUCTURED 



LATTE
MATT



BROWN
MATT



LATTE
POLISHED



BROWN
POLISHED



LATTE
STRUCTURED



BROWN
STRUCTURED





METAL
MATT



R9




BLACK
MATT




R9



METAL
POLISHED



BLACK
POLISHED



METAL
STRUCTURED



R10




BLACK
STRUCTURED



R10

SIZES



60x60
24"x24"



30x60
12"x24"



30x30
12"x12"




R9/R10

FINISH
MATT
POLISHED
STRUCTURED

COLORS
WHITE
IVORY
BEIGE
GREY
LATTE
BROWN
METAL
BLACK

DECORS



HEXAGON
30x30 - 12"x12"



DIAMOND
30x30 - 12"x12"



CUBE
30x30 - 12"x12"



SLIM HEXAGON
30x30 - 12"x12"



STRIPS
30x60 - 12"x24"



STONE MOSAIC
30x60 - 12"x24"














ZIG ZAG
30x60 - 12"x24"





STONE STRIPS
30x60 - 12"x24"



















TECHNICAL CHARACTERISTICS




		TECHNICAL FEATURES	SPECIFICATION	VALUE REQUIRED	 SETSCO TESTED
REGULARITY CHARACTERISTICS		LENGTH AND WIDTH	ISO 10545-2	±0.6%	±0.02%
		THICKNESS	ISO 10545-2	±5.0%	0.76%
		SQUARENESS	ISO 10545-2	±0.6%	-0.08%
		STRAIGHTNESS OF THE EDGES	ISO 10545-2	±0.5%	0.02%
		FLATNESS	ISO 10545-2	±0.5%	0.24%
STRUCTURAL CHARACTERISTICS		WATER ABSORPTION	ISO 10545-3	≤0.5%	0.06%
		BREAKING STRENGTH	ISO 10545-4	≥1300 N	2970 N
		MODULUS OF RUPTURE		≥35 N/mm ²	50.8 N/mm ²
CHEMICAL CHARACTERISTICS		CHEMICAL RESISTANCE	ISO 10545-13	TEST METHOD AVAILABLE DECLARED VALUE	PASSED
		RESISTANCE TO STAINING	ISO 10545-14	TEST METHOD AVAILABLE DECLARED VALUE	PASSED
SAFETY CHARACTERISTICS		SLIP RESISTANCE INCLINED PLATFORM	DIN 51130	TEST METHOD AVAILABLE	R9/R10
			DIN 51097		

SIZE, WEIGHT AND PACKAGING

						
SIZE	PIECES/BOX	MQ/BOX	KG/BOX	MQ/PALLET	KG/PALLET	BOX/PALLET
60x60	4	1.44	32	51.84	1177	36
30x60	6	1.08	24	51.84	1177	48
30x30	12	1.08	24	51.84	1177	48

FORMATS

	60x60	30x60	30x30
WHITE	 	 	 
IVORY	 	 	 
BEIGE	 	 	 
GREY	 	 	 
LATTE	 	 	 
BROWN	 	 	 
METAL	 	 	 
BLACK	 	 	 

 MATT  POLISHED  STRUCTURED

THICKNESS



RECTIFIED



PLEASE PASTE YOUR NAMECARD HERE